



**1622**

## **IKALL SIMPLEBUS AUDIO SPEAKER**



SB1

Audio speaker unit for Simplebus system, complete with terminal block and digital audio management system with Eco-cancelling, watertight loudspeaker and electrets microphone, loudspeaker volume can be adjusted from the front. Complete with microprocessor and DIP SWITCH with 8 positions for programming user calls. 33Vdc power supply via special power supply unit Art. 1595. On-board electronic lock-release function (3A), plus a 10A relay. For use in modules Art. 33400, 33401 and 33402. Dimensions: 102x55x38 mm. Compatible with all Simplebus 2 functions and products. It allows call addressing for up to 120000 users. Timed lock-release inputs and door open indication.



**1622**

## IKALL SIMPLEBUS AUDIO SPEAKER

### MAIN FEATURES

Clamps	L L V+V- RTE DO PR GND SE COM NC NO
Operating temperature (°C)	-25 ÷ 55

### GENERAL DATA

Height (mm)	55.00
Width (mm)	102.00
Depth (mm)	38.00

### COMPATIBILITY

Simplebus 1 audio system	Yes
--------------------------	-----

### ELECTRICAL SPECIFICATIONS

Door release (dry contact bridge)	Yes
Door release (direct current output)	Yes