



**30008501**

**PAIR OF MICROWAVE BARRIERS, HEIGHT 1M**



Pair of Microwave barriers formed by TX and RX in Band K at 24 GHz with 4 selectable channels, in container for mounting on the ground or in pocket art. 30008533, height 1 metre, width 250mm, depth 200 mm, maximum range 250 metres with unobstructed view, supply voltage 220V AC with internal 13.8V DC / 2.5A power supply unit and compartment for battery up to 7Ah, consumption 200mA RX, 200mA TX, completely wired and with an internal tool for on-site alignment and adjustment of sensitivity and continuous delay, wiring accessories for IP54 waterproof external installation, operating temperature -25 to +50°C, output relay for alarm and tampering.



**30008501**

## PAIR OF MICROWAVE BARRIERS, HEIGHT 1M

### MAIN FEATURES

Type	Pair of microwave barriers
Type of Detection	Microwave K-band 24Ghz
Maximum indoor distance (m)	250
Maximum outdoor distance (m)	250
Minimum distance	10m (due to microwave)
Microwave frequency (GHz)	24
Modulation channels MW	4 switchable/selectable
Barrier beams height control	Yes
Optical test indicator	Yes
Walk test function	Yes
Heaters	Yes
Tamper protection	Yes

### HARDWARE SPECIFICATIONS

Operating temperature (°C)	-25 ÷ 65
Height (mm)	1000
Width (mm)	250
Depth (mm)	200
Weight (g)	10000
Floor mounting	Yes
For outdoor use	Yes
For indoor use	Yes
Degree of protection	IP54
Barrier height (m)	1.00

### ELECTRICAL SPECIFICATIONS

Maximum current absorption	200 (Tx), 200 (Rx)
----------------------------	--------------------

The technical specifications are subject to change without prior notice.



**30008501**

**PAIR OF MICROWAVE BARRIERS, HEIGHT 1M**

**ELECTRICAL SPECIFICATIONS**

Supply voltage heaters

24VAC



**30008501**

## **PAIR OF MICROWAVE BARRIERS, HEIGHT 1M**

### **ACCESSORIES**



**30008533 POCKET FOR X1, X2, M2, M3 BARRIERS**

Modular pocket for X1, X2, M2 and M3 outdoor barriers with floor adjustment.