



4680BM

A/V unit w/facility for BM-S2 module



audio-video unit for Simplebus 2 system with Audio Induction Loop, complete with front-adjustable wide-angle 1/4" CCD colour camera and LED camera illumination. Complete with terminal block and digital audio management system with Echo-cancelling, watertight loudspeaker and electret microphone, speaker volume control on front panel. Complete with microprocessor and DIP SWITCH with 8 positions for programming calls to users. Audio-visual indications for disabled individuals assistance request can be activated via programming. 33 Vdc power supply via special power supply unit art. 1595. On-board electronic lock-release function (3A), plus a 10A relay. To be added to modules art. 33410, 33411 and 33412. Dimensions: 102x55x38 mm. Compatible with all Simplebus 2 functions and products. It can be used for the call addressing of up to 120,000 users. Timed lock-release input and door open indication.



4680BM

A/V unit w/facility for BM-S2 module

MAIN FEATURES

Camera	Colours
Horizontal resolution (tvl)	350
Minimum illumination (lux)	0.50
Operating temperature (°C)	-25 ÷ 55
Video output	1Vpp 75PAL

SOFTWARE/FIRMWARE SPECIFICATIONS

Video resolution (H x V - pixel)	500x582
----------------------------------	---------

HARDWARE SPECIFICATIONS

Visual signalling	Yes
Acoustic signalling	Yes

GENERAL DATA

Height (mm)	55.00
Width (mm)	104.00
Depth (mm)	35.00

COMPATIBILITY

Simplebus 2 audio/video system	Yes
--------------------------------	-----

ELECTRICAL SPECIFICATIONS

Maximum current absorption (mA)	400
---------------------------------	-----