



AHCAM634ZA

5MP AHD MINIDOME CAMERA, 2.8-12MM



Minidome AHD/TVI/CVI/CVBS Day & Night colour camera, 2.8-12 mm motorized zoom lens, 5 megapixel resolution, case IP66 waterproof, 24 SMD infrared leds with range of up to 35 meters.



AHCAM634ZA

5MP AHD MINIDOME CAMERA, 2.8-12MM

MAIN FEATURES

Camera sensor	1/2.9" CMOS Sony
Effective pixels (H x V - pixels)	2560x1944
Camera lens	2.8÷12mm, motorized, autofocus
Horizontal FoV (°)	26÷71 (AHD/TVI/CVI) / 32÷87 (CVBS)
Vertical FoV (°)	20÷40 (AHD/TVI/CVI) / 22÷55 (CVBS)
Electronic shutter (s)	1/25÷1/10000
Camera optical zoom	4x
Sensitivity (lux)	0.01 (colour), 0 (B/W, led IR ON)
Signal/noise ratio (dB)	>48
IR filter	Mechanical
Video output	AHD/TVI/CVI CVBS (960H)
Video resolution (H x V - pixel)	4MP, 5MP

FUNCTIONS

Back light compensation (BLC)	BLC
Enhanced DNR control	2DNR
White balance control	ATW, AWB
Exposure control	AE

HARDWARE SPECIFICATIONS

No. IR LEDs / Max. distance	24 led SMD / 35m
Maximum cable distance RG59 / UTP (m)	300 / 100
IP protection rating	IP66

GENERAL DATA

Max absorption (W)	5.00
Diameter (mm)	119



AHCAM634ZA

5MP AHD MINIDOME CAMERA, 2.8-12MM

GENERAL DATA

Height (mm)	84.00
Weight (g)	700
Type of finish	Die-cast aluminum
Housing type	Minidome
Colour	White
Operating temperature (°C)	-10 ÷ 55
RH max operating humidity (%)	85



AHCAM634ZA

5MP AHD MINIDOME CAMERA, 2.8-12MM

ACCESSORIES



WM100SD MINIDOME WALL MOUNTING SUPPORT

Support for wall mounting of minidome cameras art. IPCAM122A, IPCAM124A, IPCAM172A, IPCAM174A, IPCAM1838A, IPCAM1848A, IPCAM184KA, AHCAM634ZA, AHCAM637C, AHCAM638AWDR, AHCAM638B, AHCAM638ZA, AHCAM639ZB, AHCAM1858ZA, AHCAM175ZA, AHCAM125A and connection boxes art. JB-100MDA and JB-100SMDA, white color.



43082 POWER SUPPLY, JACK CONNECTOR, 230VAC/12VDC, 1.33A

Plug power supply, input from 100 to 240 VAC/50-60 Hz, output 12 VDC/1.33A with jack connector.