



IPNVR104FPOE

NVR W/8 IP INPUTS 5MP (4 POE), 1TB HDD



Stand-alone NVR with 8 IP inputs 5MP (4 PoE), ONVIF 2.2 compatible.



IPNVR104FPOE

NVR W/8 IP INPUTS 5MP (4 POE), 1TB HDD

MAIN FEATURES

Video inputs	8 (4 PoE 3/5MP+4 3/5MP)
Main video output	1 (VGA), 1 (HDMI) - 1920x1080@60Hz, 1280x1024@60Hz
Alarm Inputs/Outputs	2/1
Video compression	H.264, MJPEG/16÷8000 kbps
Playback / recording frame rate	120fps@5MP real time
HDD supplied size	1TB (8TB max)

SOFTWARE/FIRMWARE SPECIFICATIONS

Operating system	Linux embedded
Recording methods	Auto, manual, scheduled, motion
Recording type	Dual streaming
Maximum number of channels being played simultaneously	1@5MP/3MP, 4@Full-HD, 8@sub stream
Protocols supported	Comelit DNS, DDNS, DHCP, HTTP, ONVIF 2.2, SMTP, TCP/IP, UPnP
IP assignment	Manual, DHCP
Max bandwidth (Mbps)	50
Remote control via browser	Internet Explorer, Firefox, Chrome, Safari
Remote control by software	Comelit View 100 (Windows)
Remote control by mobile	App Comelit View 100 (Android, iOS)
Users connected at the same time	8 (70 Mbps max)
Main functions	Watermarking, Video analysis (only with dedicated cameras), Dual password authentication, Instant playback function

FUNCTIONS

Motion detection (zones)	396
Anti-tampering	Yes
Loss of video signal	Yes



IPNVR104FPOE

NVR W/8 IP INPUTS 5MP (4 POE), 1TB HDD

FUNCTIONS

Maximum number of event log (n°)	9999
Gestion PTZ par RS485 (protocoles Pelco-P, Pelco-D)	Yes
E-mail notification	Yes

HARDWARE SPECIFICATIONS

Type of connections/ports	1xEthernet 10/100 Mbit/s, 4xEthernet 10/100 Mbit/s PoE (IEEE 802.3af), 2xUSB 2.0, 1xRS485
---------------------------	---

GENERAL DATA

Max absorption (W)	16
Supply voltage (VAC)	100÷240, 50÷60Hz
Height (mm)	48.50
Width (mm)	300.00
Depth (mm)	209.00
Weight (g)	2600.00
Type of finish	Metallic
Colour	Black
Operating temperature (°C)	-10 ÷ 55
RH max operating humidity (%)	90
Supplied accessories	Power supply, Mouse