



IPNVR108FPOESL

NVR W/16 IP INPUTS 5MP (8 POE), NO HDD



Stand-alone NVR with 16 PoE IP inputs 5MP (8 PoE), ONVIF 2.2 compatible.



IPNVR108FPOESL

NVR W/16 IP INPUTS 5MP (8 POE), NO HDD

MAIN FEATURES

Video inputs	16 (8 PoE 3/5MP+8 3/5MP)
Main video output	1 (VGA), 1 (HDMI) - 1920x1080@60Hz, 1280x1024@60Hz
Alarm Inputs/Outputs	2/1
Video compression	H.264, H.265, MJPEG/16÷8000 kbps
Playback / recording frame rate	240fps@5MP real time
Additional Hard Disks (SATA)	2 (2x8TB max)

SOFTWARE/FIRMWARE SPECIFICATIONS

Operating system	Linux embedded
Recording methods	Auto, manual, scheduled, motion
Recording type	Dual streaming
Maximum number of channels being played simultaneously	1@5MP/3MP, 4@Full-HD, 8@sub stream
Protocols supported	Comelit DNS, DDNS, DHCP, HTTP, ONVIF 2.2, SMTP, TCP/IP, UPnP
IP assignment	Manual, DHCP
Max bandwidth (Mbps)	50
Remote control via browser	Internet Explorer, Firefox, Chrome, Safari
Remote control by software	Comelit View 100 (Windows)
Remote control by mobile	App Comelit View 100 (Android, iOS)
Users connected at the same time	8 (70 Mbps max)
Main functions	Watermarking, Video analysis (only with dedicated cameras), Dual password authentication, Instant playback function

FUNCTIONS

Motion detection (zones)	396
Anti-tampering	Yes
Loss of video signal	Yes



IPNVR108FPOESL

NVR W/16 IP INPUTS 5MP (8 POE), NO HDD

FUNCTIONS

Gestion PTZ par RS485 (protocoles Pelco-P, Pelco-D)	Yes
---	-----

E-mail notification	Yes
---------------------	-----

HARDWARE SPECIFICATIONS

Type of connections/ports	2xUSB 2.0, 1xRS485, 8xEthernet 10/100 Mbit/s PoE (IEEE 802.3at, 80W max)
---------------------------	--

GENERAL DATA

Max absorption (W)	18
--------------------	----

Supply voltage (VAC)	100÷240, 50÷60Hz
----------------------	------------------

Height (mm)	48.00
-------------	-------

Width (mm)	360.00
------------	--------

Depth (mm)	243.00
------------	--------

Weight (g)	2600.00
------------	---------

Type of finish	Metallic
----------------	----------

Colour	Black
--------	-------

Operating temperature (°C)	-10 ÷ 55
----------------------------	----------

RH max operating humidity (%)	90
-------------------------------	----

Supplied accessories	Power supply, Mouse
----------------------	---------------------