



IPNVR004S05PA

NVR 4CH, 5MP, POE, 1TB HDD



Stand-alone NVR with 9 IP inputs 5MP (4 PoE), ONVIF 2.4 compatible.



IPNVR004S05PA

NVR 4CH, 5MP, POE, 1TB HDD

MAIN FEATURES

Video inputs	9 (5MP, 4PoE)
Main video output	1 (HDMI), 1 (VGA), 1920x1080@60Hz
Video compression	H.264 / H.264+ / H.265 / H.265+ (64÷15000 kbps)
Playback / recording frame rate	9 (5MP / 4MP / 3MP / FULL-HD / HD) @25fps
HDD supplied size	1TB (8TB max)

SOFTWARE/FIRMWARE SPECIFICATIONS

Operating system	Linux embedded
Recording methods	Auto, manual, scheduled, motion
Recording type	Dual streaming
Maximum number of channels being played simultaneously	1 (5MP / 4MP@30fps), 2 (3MP@30fps), 4 (FULL-HD / HD@30fps)
Protocols supported	Comelit DNS, DDNS, DHCP, FTP, HTTP, NTP, ONVIF 2.4, P2P, PPPoE, RTSP, SMTP, TCP/IP, UPnP, RTP, RTCP
IP assignment	Manual, DHCP
Encrypted transmission	SSL
Max bandwidth (Mbps)	60
Remote control via browser	Internet Explorer
Remote control by software	Comelit Smart CMS
Remote control by mobile	app Comelit View Smart (Android, iOS)
Users connected at the same time	3
Main functions	Watermarking, Digital zoom, Instant playback function

FUNCTIONS

Motion detection (zones)	396
Privacy zones (n°)	3
Loss of video signal	Yes



IPNVR004S05PA

NVR 4CH, 5MP, POE, 1TB HDD

FUNCTIONS

System log	Yes
E-mail notification	Yes
Pre-event recording	5 ÷ 30 seconds

HARDWARE SPECIFICATIONS

Type of connections/ports	1xEthernet 10/100 Mbit/s, 2xUSB 2.0, 4xEthernet 10/100 Mbit/s PoE (IEEE 802.3af, 50W max)
---------------------------	---

GENERAL DATA

Max absorption (W)	65
Supply voltage (VAC)	100 ÷ 240, 50 ÷ 60Hz
Height (mm)	43.00
Width (mm)	260.00
Depth (mm)	215.00
Weight (g)	2500.00
Type of finish	Metallic
Colour	Black
Operating temperature (°C)	-10 ÷ 55
RH max operating humidity (%)	90
Supplied accessories	Power supply, Mouse
System backup	USB 2.0