



**AHDVR004S02ASL**

**XVR 4 INPUTS 2MP, NO HDD**



Stand-alone 5-hybrid (AHD/TVI/CVI/CVBS/IP) DVR, 4 analog video inputs or 2 analog video inputs and 7 IP video inputs or 16 IP video inputs.



**AHDVR004S02ASL**

**XVR 4 INPUTS 2MP, NO HDD**

**MAIN FEATURES**

Video inputs	4 BNC / 16 IP (5MP max) / 2 BNC+7 IP (5MP max)
Main video output	1 (HDMI), 1 (VGA)
Audio Inputs/Outputs	4 (RCA) / 1 (RCA), G.711u, 64 kbps
Video compression	H.264 / H.264+ / H.265 / H.265+ (128÷8192 kbps)
Playback / recording frame rate	BNC: 4 (5MP@6fps, 4MP@8fps, 3MP@9fps, 2MP@15fps, HD@25fps). IP: 8 (5MP), 12 (4MP), 16 (3MP, 2MP, HD) @25fps
Additional Hard Disks (SATA)	1 (8TB max)

**SOFTWARE/FIRMWARE SPECIFICATIONS**

Operating system	Linux embedded
Recording methods	Auto, manual, scheduled, motion
Recording type	Dual streaming
Maximum number of channels being played simultaneously	BNC: 4 (5MP@6fps, 4MP@8fps, 3MP@9fps, 2MP@15fps, HD@25fps). MIX: 1 (5MP, 4MP, 3MP)@25fps, 2 (2MP@30fps), 3 (2MP@15fps). IP: 1 (5MP, 4MP, 3MP)@30fps, 4 (2MP, HD)@30fps
Protocols supported	Comelit DNS, DDNS, DHCP, FTP, HTTP, NTP, PPPoE, RTSP, SMTP, TCP/IP, UPnP, RTP, RTCP
IP assignment	DHCP, manual
Encrypted transmission	SSL
Max bandwidth (Mbps)	48
Remote control via browser	Internet Explorer
Remote control by software	Comelit Smart CMS
Remote control by mobile	app Comelit View Smart (Android, iOS)
Users connected at the same time	3
Main functions	Camera control through coax cable via UTC protocol, Watermarking, Instant playback function

**FUNCTIONS**



**AHDVR004S02ASL**

**XVR 4 INPUTS 2MP, NO HDD**

Motion detection (zones)	396
Privacy zones (n°)	3
Loss of video signal	Yes
Gestion PTZ par RS485 (protocoles Pelco-P, Pelco-D)	Yes (Pelco-P, Pelco-D)
Digital effects	E-zoom
System log	Yes
E-mail notification	Yes
Pre-event recording	5 ÷ 30 seconds

**HARDWARE SPECIFICATIONS**

Type of connections/ports	1xEthernet 10/100 Mbit/s, 2xUSB 2.0, 1xRS485
---------------------------	--

**GENERAL DATA**

Max absorption (W)	10
Power supply voltage (VDC)	12
Supply voltage (VAC)	100 ÷ 240, 50 ÷ 60Hz
Height (mm)	43.00
Width (mm)	215.00
Depth (mm)	260.00
Weight (g)	2000.00
Type of finish	Metallic
Colour	Black
Operating temperature (°C)	-10 ÷ 55
RH max operating humidity (%)	90
Supplied accessories	Power supply, Mouse
System backup	USB 2.0