



4680CW

D&N WIDE ANGLE COLOR A/V UNIT. IKALL SERIES SIMPLEBUS



SB1

Audio/video unit with terminal block, Simplebus 2 system, complete with colour camera with 2.3 mm lens and IR illumination. Digital audio management system with Echo-cancelling, watertight loudspeaker and electret microphone, loudspeaker volume can be adjusted from the front. Complete with microprocessor and dip-switch with 8 positions for programming calls to users. Programmable audiovisual indications to comply with DDA. 33 VDC power supply via power supply unit part. 1595. On-board electronic lock-release function (3A), plus C-NC-NO 10A relay contacts. Compatible with all Simplebus 2 functions and products. Allows call addressing up to 120000 users. Timed door opening and door open visualization. To add in the audio-video modules with 0, 1 and 2 buttons. Dimensions: 4.02"x2.17"x1.5"mm.



4680CW

D&N WIDE ANGLE COLOR A/V UNIT. IKALL SERIES SIMPLEBUS

MAIN FEATURES

Camera	Colors
Diagonal viewing angle (°)	105
Horizontal resolution (tvl)	520
Minimum illumination (lux)	0.10
Lens size (inch) (mm)	2.30
Clamps	L L V+V- RTE DO PR GND SE COM NC NO
Microphone	Yes

HARDWARE SPECIFICATIONS

Visual signalling	Yes
Acoustic signalling	Yes
Speech synthesis	Yes

GENERAL DATA

Height (inch) (mm)	55.00
Width (inch) (mm)	104.00
Depth (inch) (mm)	35.00

COMPATIBILITY

Simplebus 2 audio/video system	Yes
--------------------------------	-----

ELECTRICAL SPECIFICATIONS

Door release (dry contact bridge)	Yes
Door release (direct current output)	Yes